

MkV 1350mm Wide Servo Pre-Stretch Semi-Automatic Rewinding Machine



Specification

- ❑ MKV base frame with geared stretcher train to give a stretch of 335%
- ❑ Servo driven rewind to vary tension from 240% to 335%.
- ❑ Variable speed drive up to 350 m/min when stretching
- ❑ Maximum master roll web width 1350mm
- ❑ Single position rewind arms equipped with 38, 50mm or 76mm collets
- ❑ Slitting option (shown) to allow two or three prestretched rolls to be converted from a 1350mm wide master roll
- ❑ Manually adjusted pneumatic core pressure
- ❑ Programmable electronic counter unit
- ❑ Stretch ratio programmed on the front panel to control the servo rewind drive
- ❑ Film break sensor
- ❑ Maximum rewind roll diameter 280mm subject to film type
- ❑ Maximum parent roll diameter 500mm.
- ❑ 3 - phase 200 or 400 volt supply
- ❑ Air requirements - 4 cfm max. at 80 psi.
- ❑ Guarding to suit current C.E. requirements

Machine Features



Geared prestretch roller train.



Front arm loading.



Multi Product capability



CG Automatic Converting Equipment Ltd

8 Highmeres Rd
Leicester LE4 9LZ
England
Ph +44 116 2760206 Fax +44 116 2742995

Designing, Manufacturing & Supplying

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators &
Special Purpose Machines.

sales@cga-converting.com / www.cga-converting.com