

Automatic 'Hand & Band' Rewind Slitting Machine



Specification

- ❑ Maximum parent roll width 760mm (30'') Diameter 450mm (18'')
- ❑ Accepts parent rolls on 76mm (3'') I.D. cores.
- ❑ Master roll lifting table.
- ❑ Five adjustable slitting blades
- ❑ Interchangeable steering unit (mountings only)
- ❑ Rewinding capability from full width to 76mm (3'').
- ❑ Adjustable external electronic rewind tension from **-3% to +5%** in increments of **0.1%**
- ❑ Variable speed drive of up to 1000m (3000') **per minute**.
- ❑ Programmable electronic length counter.
- ❑ Automatic core feed hopper.
- ❑ Single turret rewind arm.
- ❑ Automatic film cut off & attachment.
- ❑ Rewind roll maximum diameter 240mm
- ❑ Maximum core width 810mm (32'').
- ❑ Minimum core width 82mm (3.25'')
- ❑ Rewind core diameter 50mm *other sizes with change parts*.
- ❑ Finished roll storage table.
- ❑ 3 - phase 220-400 volt 50-60Hz supply. / Air requirements - 4 cfm max. at 80 psi.



CG Automatic Converting Equipment Ltd

8 Highmeres Rd
Leicester LE4 9LZ
England
Ph +44 116 2760206 Fax +44 116 2742995

Designing, Manufacturing & Supplying

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators & Special Purpose Machines.

sales@cga-converting.com / www.cga-converting.com